

MOTO FORK OIL 5W & 10W



MOTORCYCLE

Lubricants

Description

Hydraulic oil for motorcycle forks and shock absorbers. It has exceptional shearing resistance and is suitable for sports and urban use. It has excellent antioxidant, anticorrosion and antiwear properties. It releases the air bubbles produced in shock absorber systems by maintaining homogeneous and smooth behaviour at all times within a wide range of temperatures..

Properties

- Good performance when faced with changes in temperature due to its high viscosity index.
- Good shock absorbing characteristics and compatibility with oil seals.
- Excellent anti-friction performance thanks to its special additives.
- Great resistance to ageing and good anti-rusting and anticorrosive properties.

Quality Levels

- DIN 51524 Part 2

Technical specifications

| | UNIT | METHOD | VALUE | |
|-----------------------|-------------------|-------------|-------|-------|
| SAE Grade | | | 5W | 10W |
| Density at 15 °C | g/cm ³ | ASTM D 4052 | 0.875 | 0.845 |
| Viscosity at 100 °C | cSt | ASTM D 445 | 4.9 | 8.3 |
| Viscosity at 40 °C | cSt | ASTM D 445 | 22 | 46 |
| Viscosity at -25 °C | cp | ASTM D 5293 | <6000 | <6000 |
| Viscosity index | - | ASTM D 2270 | 150 | 157 |
| Flash point, open cup | °C | ASTM D 92 | 200 | 232 |
| Pour point | °C | ASTM D 97 | -54 | -40 |

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 3. October 2016.