

# MOTO TRANSMISSION TRIAL 75W

MOTORCYCLE

Lubricants



## Description

Synthetic oil for transmissions of motorcycles developed with the experience of our racing teams. It improves substantially the quickness and precision of the gearshift, enhancing at the same time the smoothness and progressivity of the clutch. This lubricant is specially recommended in severe driving conditions.

## Properties

- It has excellent oxidation stability, even in extreme high temperature conditions, thus making the product more durable, which enables long drainage periods
- Its excellent fluidity at low temperature enables speed and clutch changes to be carried out smoothly and precisely
- Maximum protection against wear for all parts of the gearbox, which enhances the durability of the mechanisms.
- Proof of performance in trial motorcycles
- It is also valid for use in the gearbox of passenger cars or light duty models when this viscosity is required

## Quality Levels

- API GL-4 / GL-5

## Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0.841
Viscosity at 100 °C	cSt	ASTM D 445	5.0
Viscosity at 40 °C	cSt	ASTM D 445	24
Viscosity at -40 °C	cP	ASTM D 2983	4000.
Viscosity index	-	ASTM D 2270	146
Flash point, open cup	°C	ASTM D 92	170 min
Pour Point	°C	ASTM D 97	-69
T. B. N.	mg KOH/g	ASTM D 2896	4.5

A safety information file is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 8 September 2016