

**RIDER TOWN 4T 20W-50****MOTO**

## Description

Refined lubricant oil especially designed for 4-stroke petrol engine motorcycles the greater part of whose activity is developed in an urban environment. Its additives prolong its life in this type of working conditions.

## Properties

- Guarantees good lubrication in normal service conditions
- Prevents the formation of lacquers and varnishes thanks to its dispersant additives.
- Its degree of viscosity guarantees perfect performance in warm atmospheres.
- Its detergency ensures the piston is properly cleaned.
- It maintains an adequate pressure and temperature under all service conditions.

## Quality levels, approvals and recommendations

- API SJ
- JASO T 903:2016 MA2\*
- \*Formal approval

## Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			20W-50
Density at 15 °C	g/cm3	ASTM D 4052	0,888
Viscosity at 100 °C	cSt	ASTM D 445	19
Viscosity at 40 °C	cSt	ASTM D 445	166
Viscosity at -15 °C	cP	ASTM D 5293	9500 maximum
Viscosity index	-	ASTM D 2270	
Flash point, open cup	°C	ASTM D 92	248
Pour point	°C	ASTM D 97	-24
T.B.N.	mg KOH/g	ASTM D 2896	7
Bosch injector shearing:			
Viscosity at 100 °C after shear	cSt	CEC-L014-93	16,3 minimum
Noack volatility, 1hr at 250 °C	% weight	CEC-L-40-93	6,2
HTHS, viscosity at 150 °C	cP	CEC-L-36-A-90	3,7 minimum

The above mentioned characteristics are typical values and should not be considered product specifications.